



280KG(600LBS) Electric Magnetic Lock (Surface Mounted)

Features


1. With LED lights on. SM-280-S has Signal output to indicate the lock status (monitored)
2. Low current consumption
3. Reliable holding force
4. High strength material, anodized aluminum housing
5. Anti-residual magnetism designed
6. Durable and silence operation
7. CE Certificate by European Union

Specification


Model	SM-280 / SM-280-S (Signal output) / SM-280-T (Signal output and time delay)
Feature	Fail-safe: Power to lock. (Signal output, monitored), time delay: 0,3,6 second delay
Lock Size	250 L X 25 H X 47 D (mm)
Armature Size	180 L X 38 H X 11 D (mm)
Holding Force	280KG(600LBS)
Voltage	DC12V
Current Draw	12V/380mA
Material	Finishes for shell: Anodized aluminum Finishes for magnet: Zinc Finishes for Armature: Zinc
Certification	CE, ROHS
Advantage	Low power consumption, high efficiency
Application	Metal doors, wooden doors, fireproof doors, glass door
Weight	Approx.: 1.8kg

Packing


Carton Size: 30X30X22 cm Qty/Carton: 12pcs N.W: 21.0KG G.W: 21.7KG




Standard Installation



LS Bracket Installation



ZL Bracket Installation



U Bracket Installation