


PARAMETER: SDC-12D2E

<b>PARAMETER</b>	<b>MODEL PICTURE</b>		<b>SDC-12D2E</b>
			<b>AC/DC ADAPTER</b>
			<b>12V2A</b>
<b>Input</b>	Input Connecting plug	Europe /70mm	
	Input voltage	AC100-240V50/60Hz	
<b>Output</b>	Output Connector	Standard 5.5 X 2.1mm DC/70mm, others	
	Output voltage	12V + / - 5 %	
	Output electric current	2A	
	Ripple wave	<90 (mVp-p)	
	Linear modulate	±0.5%max	
	Temperature coefficient	±0.02%/°C	
	start time	≤3s(240VAC output, lo=100%)	
	guard time	≥20ms(240VAC input, lo=100%)	
	Output Standard	12V2A	
<b>Protection</b>	override protection	115%~200%kvA, automatic recovery	
	short-circuit protection	1 channel: automatic recovery	
<b>Insulation</b>	insulation strength	1000VAC/10mA, 1MIN	
	insulation resistance	≥30MΩ, DC 500V	
<b>Environment</b>	working temperature	0°C~40°C, 10%~90%RH	
	Store temperature	-20°C~60°C, 10%~90%RH	
<b>Size</b>	Size/ weight	86*45*28.3mm/170G	
	Package	100PCS/Carton	