


PARAMETER: **SDC-12D3E**

<b>PARAMETER</b>		<b>MODEL PICTURE</b>		<b>SDC-12D3E</b>
				<b>AC/DC ADAPTER</b>
				<b>12V3A</b>
<b>Input</b>	Input Connecting plug	Europe AC cable /70mm		
	Input voltage	AC100-240V50/60Hz		
<b>Output</b>	Output Connector	Standard 5.5 X 2.1mm DC/150mm, others		
	Output voltage	12V + / - 5 %		
	Output electric current	3A		
	Ripple wave	<90 (mVp-p)		
	Linear modulate	±0.5%max		
	Temperature coefficient	±0.02%/°C		
	Efficiency	>80 %		
	start time	≤3s (240VAC output, lo=100%)		
	guard time	≥20ms (240VAC input, lo=100%)		
	Output Standard	12V3A		
<b>Protection</b>	override protection	115%~200%kvA, automatic recovery		
	short-circuit protection	1 channel: automatic recovery		
<b>Insulation</b>	insulation strength	1000VAC/10mA, 1MIN		
	insulation resistance	≥30MΩ, DC 500V		
<b>Environment</b>	working temperature	0°C~40°C, 10%~90%RH		
	Store temperature	-20°C~60°C, 10%~90%RH		
<b>Size</b>	Size / weight	110*44*32mm/250G		
	package	100PCS		